

DS303C215

NEW

China DTTB Modulation Option (SAC GB20600-2006 standards)

■ General

The DS303C215 is a modulation unit conforming to DTTB (*1) China terrestrial digital broadcasting standards (GB20600-2006) promulgated by the Standardization Administration of China in August 2006.

The DS303C215 supports all 330 kinds of transmission parameter required by China DTTB standards.

When the DS303C215 is installed on the DS303 series main frame together with the modulation unit, the DS303 series main frame can generate the terrestrial digital television broadcasting signal conforming to China DTTB standards.



DS303 series mainframe

*1: Digital Television Terrestrial Broadcasting

■ Features

- ◆ Supports all 330 kinds of transmission parameter required by China DTTB standards.
 - ◆ Noise signal can be added. (CN 0.0 to 30.0dB, 0.1dB step)
 - ◆ BER (Bit Error Rate) measurement is available.
 - ◆ The other digital modulation systems including ATSC, SCTE (USA-QAM, Annex B), DVB-T, DVB-C (Annex A), ISDB-T and ISDB-C (Annex C) can be installed on the same DS303 series main frame.
- One set of DS303 Series can generate world wide digital TV broadcasting signal.

■ Specifications

- | | |
|-----------------------|---|
| ◆ Standards | DTTB China terrestrial digital broadcasting (SAC GB20600-2006) |
| ◆ Band width | 8MHz |
| ◆ Carrier mode | Multi, Single-P0, Single-P2 |
| ◆ Modulation scheme | 4QAM-NR, 4QAM, 16QAM, 32QAM, 64QAM |
| ◆ Guard Interval | 420 Symbols, CP420 Symbols, 595 Symbols, 945 Symbols, CP945 Symbols |
| ◆ LDPC rate | 0.4, 0.6, 0.8 |
| ◆ Time interleave | 240 symbols, 720 symbols |
| ◆ Input signal | DVB-SPI (D-SUB25, Female) |
| ◆ Output signal | IF signal (BNC-J 75ohm) |
| ◆ IF output level | -15.0dBm +/- 5dB (0.1dB step) |
| ◆ IF output frequency | 44.000000MHz +/- 200kHz (1Hz step) |
| ◆ Test pattern | PRBS9, PRBS11, PRBS15, PRBS20, PRBS23, Ramp, Fixed 00Hex, Fixed 55Hex, Fixed AAHex, Fixed FFHex |

ShibaSoku Co.,Ltd.

International Sales Dept.

3-2, Hisamoto 3-chome, Takatsu-ku, Kawasaki-shi, Kanagawa, 213-0011 Japan

Phone: +81-44-850-5133 Fax: +81-44-850-5134

ShibaSoku Taiwan Co., Ltd.

5F, No.39, Shi-Wei St., San-Chung City, Taipei Hsien, Taiwan

Phone: +886-2-8985-0960 Fax: +886-2-8985-1306

Asaca/ShibaSoku Corp. of America

450 Donald J. Lynch Blvd., Suite D, Marlborough, MA 01752, U.S.A.

Phone: +1- 508-229-0107 Fax: +1- 508-229-0721 URL: <http://www.asaca.com>

Mail to: info@shibasoku.co.jp

URL: <http://www.shibasoku.com/>